

Table 23

BRAKES, FRONT WHEEL BRAKE

Group 42

Fig. No.	No. of spare part	Denomination	Quantity	Remarks
15	180 993 23 01	Pressure spring	4)
16	-	Washer 5, 3 DIN 125	4)for guide pin
17	-	Cotter pin 3 x 15 DIN 94	4)at brake anchor
18	120 993 08 10	Release spring (for brake shoe, front)	4)plate
		<u>WHEEL BRAKE CYLINDER, FRONT</u>)
25	000 420 72 18	Wheel brake cylinder 28,57 ϕ =1 1/8" with sheet metal protective cap (for front wheel brake, left)	2	
26	000 420 73 18	Wheel brake cylinder 28,57 ϕ =1 1/8" with sheet metal protective cap (for front wheel brake, right)	2	
27	000 421 10 90	Stop spring	4	
28	000 421 14 89	Filling piece	4	
29	000 421 05 86	Sealing sleeve	4	
30	000 421 16 83	Piston	4	
31	000 421 10 87	Protective cap	4	
32	000 421 09 88	Pressure pin	4	
32a	000 421 16 87	Sheet metal protective cap	4	
33	000 420 08 55	Bleeder screw	2	
34	000 421 08 87	Rubber cap	2	

Table 23

BRAKES, FRONT WHEEL BRAKE

Group 42

Fig. No.	No. of spare part	Denomination	Quantity	Remarks
35	-	Lock washer B 8 DIN 127	12)for wheel
36	-	Hex. -hd. screw M 8x15 DIN 933-8 G	12)brake cylinder)at brake anchor)plate
<u>BRAKE FLUID LINES</u>				
40	180 420 07 29	Brake fluid line, left (from distributor fitting to wheel brake cylinder, left)	1	
41	180 420 08 29	Brake fluid line, right (from distributor fitting to wheel brake cylinder, right)	1	
42	-	Hex. -hd. screw M 7x22 DIN 931-8 G	4))for brake fluid)line at brake
43	-	Lock washer B 7 DIN 127	4)anchor plate)
44	-	Hex. nut M 7 DIN 934-5 S	4)
45	180 420 08 28	Brake fluid line (between the two wheel brake cylinders)	2	
46	000 428 07 26	Hollow screw	6	
47	-	Sealing ring A 10x14 DIN 7603 Cu	12	
47a	180 987 00 37	Rubber pad	2	
48	180 421 03 18	Pin (for brake shoe suspension)	4))for pin at)brake anchor
49	-	Lock washer B 12 DIN 127	4)plate

Table 23

BRAKES, FRONT WHEEL BRAKE

Group 42

Fig. No.	No. of spare part	Denomination	Quantity	Remarks
50	-	Hex. nut M 12x1, 5 DIN 936-5 S (for pin at brake anchor plate)	4	
51	120 421 02 56	Washer	4)
-	120 421 03 56	Shim 0.50 mm thick)	a.r.))
-	120 421 04 56	Shim 0.75 mm thick) optional	a.r.))
-	120 421 05 56	Shim 0.88 mm thick)	a.r.)) for brake shoes at pin
52	120 990 07 40	Washer	4)
53	-	Lock washer B 8 DIN 127	4)
54	-	Hex. -hd. screw M 8x12 DIN 933-8 G	4)