

Designation	Order No.
Puller for chain guide pivot pin	187 589 07 33
Puller for camshaft sprocket	187 589 01 33
Gage for checking the alignment of sprockets	187 589 02 23
Puller for idling gear	187 589 02 35
Tool for the removal and installation of idling gear shaft and for the installation of the idling gear	187 589 07 61
Puller for the rear bearing bushing of the idling gear / distributor drive	186 589 09 33
Dismantling tool for opening endless chains	000 589 03 25
Fuel feed pump tester	000 589 30 21
Puller for the water pump seal retainer	136 589 33 33
Forcing sleeve and arbor for the impeller and the water pump shaft	187 589 01 35
Fitting sleeve for the water pump seal	187 589 07 39
Fitting sleeve for the water pump annular grooved bearing	187 589 04 39
Fitting sleeve for forcing on the water pump retainer ring	187 589 08 39
Fitting sleeve for the water pump seal retainer	180 589 09 39
Fitting sleeve for the water pump spacer ring and ventilator hub	187 589 09 39
Puller for the counterweight of the crankshaft and the pulley of the water pump	000 589 17 33
Bell-shaped puller for the crankshaft sprocket	187 589 00 33
Puller for the bearing cover and for the ball bearing of the crankshaft (flywheel side)	136 589 07 33
Arbor fixture for balancing the flywheel	180 589 00 27
Static balancer for balancing the flywheel	000 589 15 21
Cylinder inspection lamp	000 583 11 19
Internal micrometer for 50—100 mm ϕ (for cylinder bores, crankshaft and connecting rod bearings, etc.)	000 589 04 19
Internal micrometer for 35—60 mm ϕ (for camshaft bearing bore)	000 589 03 19
Internal micrometer for 18—35 mm ϕ (for piston pin bushing bore)	000 589 02 19
Micrometer for 0—25 mm ϕ for measuring washers etc.	000 589 06 19
Micrometer for 25—50 mm ϕ for camshaft bearing surfaces	000 589 07 19
Micrometer for 50—75 mm ϕ for crankshaft bearing surfaces	000 589 08 19
Micrometer for 75—100 mm ϕ for pistons etc.	000 589 09 19
Piston ring clamp 80—85 mm ϕ	121 589 00 61
Piston ring pliers 50—100 mm ϕ	000 589 00 37
Feeler gage 0.03—1.0 mm	000 581 01 30
Depth gage 160 mm long	—
Spring scale for measuring the spring tension of the rotor arm of the distributor (Kontactor GK size 6, 100—1000 g)	000 589 73 21
Scleroscope (harness tester)	000 589 20 21
Connecting rod alignment gage	—

Clutch — Group 25

Designation	Order No.
Special wrench SW 17 mm, extra long, for the screws fixing the clutch housing to the engine	000 589 05 03
3 hold-down clamps with chain for removal and installation of the clutch	136 589 23 61
Centering arbor for the clutch disk	136 589 00 61
Puller with dismantling sleeve for the throw-out bearing	136 589 25 33
Tester for valve and clutch springs	000 589 00 65 *
Depth gage 160 mm long	—
Dial gage, 10 mm travel, $\frac{1}{100}$ mm reading accuracy	000 589 14 21 *
Dial gage holder	—